## NSN 5320-00-323-3989

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-323-3989

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
1.075 inches
Head Style:
Flush countersunk
Width Between Flats:
0.080 inches
Shank Diameter:
0.190 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.377 inches and 0.381 inches
Lubrication:
Cetyl alcohol
End Application:
F-22, f-15, b-1b
Grip Length:
0.755 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 newtons per square millimeter
Thread Size:
0.190 inches
Shear Strength:
5380 double pounds per square inch
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Feat
Special Features:
Weapons system essential
Material:
Titanium
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment Specification:

Perhi-shear spec.305 mfr ref single treatment response

## NSN 5320-00-323-3989

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A528u0