# NSN 5320-00-323-3989

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-323-3989

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.075 inches

Head Style:

Flush countersunk

#### Width Between Flats:

0.080 inches

Shank Diameter:

0.190 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.377 inches and 0.381 inches

Lubrication:

Cetyl alcohol

# End Application:

F-22, f-15, b-1b

## Grip Length:

0.755 inches

# Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 newtons per square millimeter

#### **Thread Size:**

0.190 inches

## Shear Strength:

5380 double pounds per square inch

### **Countersink Angle:**

100.0 degrees

### **Criticality Code Justification:**

Feat

#### **Special Features:**

Weapons system essential

### Material:

Titanium

### Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment Specification:

Perhi-shear spec.305 mfr ref single treatment response

# NSN 5320-00-323-3989

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

