# NSN 5320-00-323-6038

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-323-6038



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.503 inches and 0.523 inches

## Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

### Width Between Flats:

Between 0.079 inches and 0.081 inches

### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

0.193 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

# Shear Strength:

125000 single pounds per square inch

# **Special Features:**

White paint on head

## Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-00-323-6038

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

