## NSN 5320-00-323-6041

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-323-6041



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.815 inches and 0.835 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.079 inches and 0.081 inches

#### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol

## End Application:

Aircraft, b-1b; aircraft, hornet f/a-18; aircraft, harrier av-8b; aircraft, eagle f-15

## Grip Length:

0.505 inches

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-00-323-6041

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

