## NSN 5320-00-323-6192



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-323-6192 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.864 inches and 0.884 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol **Grip Length:** 0.567 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** 

N/a Unit Of Measure: --

Shelf Life:

Unjc

## NSN 5320-00-323-6192

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0