

View Online at <https://aerobasegroup.com/nsn/5320-00-324-9674>

**Fastener Length:**

Between 2.129 inches and 2.139 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.3730 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, multiple grooved

**Head Major Diameter:**

Between 0.494 inches and 0.566 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 1.751 inches and 1.812 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

76.1 rockwell superficial 15-n and 80.9 rockwell superficial 15-n

**Shear Strength:**

21000 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4037 or steel comp 4140 or steel comp 8740

**Material Specification:**

Astm a547 assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas1442 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0