# NSN 5320-00-324-9723

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-324-9723

## Fastener Length:

Between 2.349 inches and 2.369 inches

## Head Style:

Err-090

# Head Height:

Between 0.194 inches and 0.224 inches

## Shank Diameter:

Between 0.3730 inches and 0.3745 inches

## Shank Style:

Pin-rivet, multiple grooved

## Head Major Diameter:

Between 0.595 inches and 0.655 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.782 inches and 1.844 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

76.1 rockwell superficial 15-n and 80.9 rockwell superficial 15-n

## Shear Strength:

21000 double pounds per square inch

## Material:

Steel comp 4037 or steel comp 4140 or steel comp 8740

## **Material Specification:**

Astm a547 assn standard all material responses

## Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Specification Data:**

80205-nas1472 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A528u0