NSN 5320-00-325-1894

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-325-1894

Fastener Length:

Between 0.428 inches and 0.448 inches

Head Style:

Undersized oval countersunk

Head Height:

Between 0.003 inches and 0.005 inches

Shank Diameter:

Between 0.093 inches and 0.096 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.126 inches and 0.148 inches

Head Minor Diameter:

Between 0.086 inches and 0.096 inches

Countersink Height:

Between 0.011 inches and 0.031 inches

Shear Strength:

36000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy

Material Specification:

Qq-a-430, comp 7050 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Specification Data:

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.