

View Online at <https://aerobasegroup.com/nsn/5320-00-330-3303>

Fastener Length:

0.665 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Shank Style:

Err-090

Head Major Diameter:

0.3988 inches

Grip Length:

Between 0.439 inches and 0.500 inches

Countersink Angle:

100.0 degrees

Heat Treatment:

Solution heat treated

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 3rd material response or mil-s-8503 military specification 4th material response or ams 6330 assn standard 5th material response or mil-s-5626 military specification all material responses or mil-s-5000 military specification 6th material response or mil-s-5000 military specification 7th material response or ams 6415 assn standard 8th material response or mil-s-8695 military specification 9th material response or mil-s-6758 military specification 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Data:

80205-nas1055 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.