

View Online at <https://aerobasegroup.com/nsn/5320-00-332-4927>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.213 inches and 0.215 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.342 inches and 0.385 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.094 inches and 0.156 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Self-locking

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1750 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.