

View Online at <https://aerobasegroup.com/nsn/5320-00-332-7398>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.173 inches and 1.203 inches

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.069 inches

Width Between Flats:

Between 0.127 inches and 0.130 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

Between 0.683 inches and 0.693 inches

Thread Size:

0.312 inches

Shear Strength:

108000 single pounds per square inch

Special Features:

Double shear strength 18200 lb

Heat Treatment:

As fabricated

Material:

Steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-5000 military specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.