

View Online at <https://aerobasegroup.com/nsn/5320-00-338-5786>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.114 inches and 1.134 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.060 inches

**Width Between Flats:**

Between 0.064 inches and 0.065 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.242 inches and 0.262 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.817 inches

**Thread Size:**

0.164 inches

**Shear Strength:**

1760 double pounds per square inch

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.