## NSN 5320-00-338-5805

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-338-5805

Thread Class.
Thread Class:
3a Through Birnerians
Thread Direction:
Right-hand  Factorial Langth:
Fastener Length:
Between 1.864 inches and 1.884 inches
Head Style:
Err-090
Head Height:
Between 0.045 inches and 0.060 inches
Width Between Flats:
Between 0.064 inches and 0.065 inches
Shank Diameter:
Between 0.1625 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.242 inches and 0.262 inches
Lubrication:
Cetyl alcohol
Grip Length:
1.567 inches
Thread Size:
0.164 inches
Shear Strength:
1760 double pounds per square inch
Heat Treatment:
T-6 solution heat treated
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5320-00-338-5805

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.