NSN 5320-00-338-5824

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-338-5824 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.635 inches and 0.655 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol **Grip Length:** 0.255 inches **Thread Size:** 0.250 inches **Shear Strength:** 4500 double pounds per square inch **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-00-338-5824

Pin-rivet - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.