

View Online at <https://aerobasegroup.com/nsn/5320-00-338-6334>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.9400 inches and 0.9600 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0640 inches and 0.0740 inches

**Width Between Flats:**

Between 0.07910 inches and 0.08060 inches

**Shank Diameter:**

Between 0.2177 inches and 0.2182 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.3700 inches and 0.3900 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.6200 inches and 0.6300 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear specification 258, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.