

View Online at <https://aerobasegroup.com/nsn/5320-00-338-6334>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.9400 inches and 0.9600 inches

Head Style:

Err-090

Head Height:

Between 0.0640 inches and 0.0740 inches

Width Between Flats:

Between 0.07910 inches and 0.08060 inches

Shank Diameter:

Between 0.2177 inches and 0.2182 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3700 inches and 0.3900 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.6200 inches and 0.6300 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.