

View Online at <https://aerobasegroup.com/nsn/5320-00-340-6635>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.375 inches and 0.400 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.171 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.236 inches

**Tip Diameter:**

0.1708 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.125 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.164 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Major diameter: 0.1717 in.

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1724 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.