NSN 5320-00-340-6704

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-340-6704 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.065 inches and 1.085 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol **Grip Length:** 0.755 inches **Thread Size:** 0.190 inches **Shear Strength:** 2540 double pounds per square inch **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-00-340-6704

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.