NSN 5320-00-347-0063

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-347-0063

Fastener Length:
0.500 inches
Head Style:
Flush countersunk
Shank Diameter:
Between 0.1870 inches and 0.1895 inches
Shank Style:
Err-090
Head Major Diameter:
0.304 inches
Grip Length:
Between 0.313 inches and 0.375 inches
Countersink Angle:
100.0 degrees
Heat Treatment:
Solution heat treated
Material:
Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel
comp 4037 or steel comp 4130
Material Specification:
Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response or mil-s-8503 military specification 3rd material response or ams 6330 assn standard 4th material response or
mil-s-5626 military specification 5th material response or mil-s-5000 military specification all material responses or mil-s-5000 military
specification all material responses or ams 6415 assn standard all material responses or mil-s-8695 military specification 6th material
response or mil-s-6758 military specification 7th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Specification Data:
80205-nas1055 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A528u0
Mil-std (military Standard):
Mil-s-6098 spec.