

View Online at <https://aerobasegroup.com/nsn/5320-00-354-6101>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.920 inches and 1.940 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.127 inches and 0.130 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.469 inches and 0.474 inches

Grip Length:

1.400 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.