

View Online at <https://aerobasegroup.com/nsn/5320-00-354-6313>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

2.078 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.4522 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.647 inches

**Grip Length:**

1.625 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

0.4219 in. Second shank dia. And lubrication cetyl alcohol

**Material:**

Steel comp 8740 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.