## NSN 5320-00-357-2151

Mil-std (military Standard):

Mil-s-5626 spec.



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-357-2151 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.274 inches and 0.276 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** Between 0.463 inches and 0.507 inches **Expansion Device:** Threaded stem **Grip Length:** Between 0.470 inches and 0.531 inches **Hardness Rating:** 39.0 rockwell c nut and 43.0 rockwell c nut **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Self-locking Material: Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut **Material Specification:** Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut **Surface Treatment:** Passivate sleeve and cadmium sleeve **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1750 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0