NSN 5320-00-358-0289

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Err-090

Head Height:

Thread Direction:

Fastener Length:

Between 0.612 inches and 0.642 inches

За



View Online at https://aerobasegroup.com/nsn/5320-00-358-0289

Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.125 inches and 0.127 inches
Shank Diameter:
Between 0.249 inches and 0.250 inches
Shank Style:
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Grip Length:
0.250 inches
Thready Qty Per Inch (tpi):
28
Hardness Rating:
51.0 rockwell c and 53.0 rockwell c
Thread Size:
0.250 inches
Shear Strength:
15300 double pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response
Surface Treatment:
Nickel and zinc
Surface Treatment Specification:
Ams 2417 assn standard all treatment responses
Thread Series Designator:
Unf
Specification Data:
80205-nas1324 professional/industrial association standard
Shelf Life:
N/a

NSN 5320-00-358-0289

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0