NSN 5320-00-365-0153

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-365-0153 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.740 inches and 0.750 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.163 inches and 0.164 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-00-365-0153

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0