# NSN 5320-00-367-6740

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-367-6740



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.260 inches and 1.280 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.095 inches and 0.097 inches

## Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.390 inches and 0.395 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.880 inches

# Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

#### Material Specification:

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

258 fscm 73197 mfr ref single treatment response or qq-p-35 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-00-367-6740

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

