NSN 5320-00-369-2923

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-369-2923

view Offilite at https://defobasegroup.com/his//5525-505-2525
Fastener Length:
Between 0.615 inches and 0.635 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.124 inches and 0.128 inches
Shank Style:
Countersunk (undrilled)
Head Major Diameter:
Between 0.2006 inches and 0.2360 inches
End Application:
W/s: aircraft, hawkeye e-2c; deep submergence systems programs (dssp); aircraft, airlifter c-17a; fms-aircraft, hawkeye e-2c
Shear Strength:
90000 single pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
Solution heat treated
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Specification Data:
80205-nas1199 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0