NSN 5320-00-369-4026

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-369-4026



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.938 inches and 0.968 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.078 inches and 0.079 inches

Shank Diameter:

Between 0.2041 inches and 0.2051 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

0.635 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

260000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Nickel and zinc

Surface Treatment Specification:

Ams 2417 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1323 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-00-369-4026

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

