

View Online at <https://aerobasegroup.com/nsn/5320-00-369-4032>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.690 inches and 1.710 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol

End Application:

W/s: aircraft, stratolifter c-135; aircraft, hawkeye e-2c; aircraft, c-2a (reprocured); helicopter, hh-53h pave low; aircraft (ac-130h, mc-130h, ec-130e, hc-130)aircraft, thunderbolt ii, a-10; aircraft, starlifter c-141

Grip Length:

1.380 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.