# NSN 5320-00-373-0942

Pin-rivet - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.740 inches and 0.760 inches

### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

### Width Between Flats:

Between 0.127 inches and 0.130 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.255 inches

# Thready Qty Per Inch (tpi):

24

### **Thread Size:**

0.312 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-00-373-0942

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

