NSN 5320-00-373-1349

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-373-1349 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.813 inches and 0.843 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.078 inches and 0.079 inches **Shank Diameter:** Between 0.2041 inches and 0.2051 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Grip Length:** 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 156000 single pounds per square inch Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Nickel and zinc

Surface Treatment Specification:

Ams 2417 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1323 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-00-373-1349

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0