

View Online at <https://aerobasegroup.com/nsn/5320-00-373-1349>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.813 inches and 0.843 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.078 inches and 0.079 inches

**Shank Diameter:**

Between 0.2041 inches and 0.2051 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Grip Length:**

0.510 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

156000 single pounds per square inch

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Nickel and zinc

**Surface Treatment Specification:**

Ams 2417 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1323 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0