

View Online at <https://aerobasegroup.com/nsn/5320-00-377-1196>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.274 inches and 0.276 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.463 inches and 0.507 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Self-locking

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 4130 nut

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response bolt

**Surface Treatment:**

Passivate and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response and qq-p-416 type 1 cl 3 federal specification 2nd treatment response sleeve

**Specification Data:**

80205-nas1750 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.