

View Online at <https://aerobasegroup.com/nsn/5320-00-395-6508>

**Fastener Length:**

Between 0.306 inches and 0.336 inches

**Head Style:**

Universal

**Head Height:**

Between 0.037 inches and 0.047 inches

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Shank Style:**

Self-plugging high clinch shank

**Head Major Diameter:**

Between 0.296 inches and 0.328 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Material:**

Steel comp 1030 mandrel or steel comp 1033 mandrel or steel comp 1034 mandrel or steel comp 1035 mandrel or steel comp 1536 mandrel or steel comp 1037 mandrel or steel comp 1038 mandrel or steel comp 1039 mandrel or steel comp 1040 mandrel or steel comp 1541 mandrel or steel comp 1042 mandrel or steel comp 1043 mandrel or steel comp 1044 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1050 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel

**Material Specification:**

66 federal standard all material responses mandrel

**Surface Treatment:**

Zinc mandrel and chromate mandrel or cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0