## NSN 5320-00-401-1944

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-401-1944 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.3960 inches and 1.4210 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3669 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.6170 inches and 0.6830 inches Tip Diameter: 0.3508 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.9900 inches and 1.0050 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 10800 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-00-401-1944

Pin-rivet - Page 2 of 2



Fiig:

A528u0