NSN 5320-00-401-2024



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-401-2024 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.396 inches and 1.421 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3826 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.552 inches Tip Diameter: 0.3651 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life: N/a

Unjf

Thread Series Designator:

NSN 5320-00-401-2024

Pin-rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.