
# NSN 5320-00-401-5694

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.427 inches and 1.447 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.0635 inches and 0.0645 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.120 inches and 1.130 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.164 inches

#### Shear Strength:

108000 single pounds per square inch

#### Criticality Code Justification:

Aaze and aatb

Material:

Titanium alloy

#### Material Specification:

Ams 4971 assn standard single material response

#### **Thread Series Designator:**

Unjc

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-00-401-5694

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

