# NSN 5320-00-401-5701

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-401-5701



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.885 inches and 0.905 inches

## Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Cetyl alcohol

Grip Length:

Between 0.495 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

108000 single pounds per square inch

## Criticality Code Justification:

Aaze

# Material:

Titanium alloy

# Material Specification:

Ams 4971 assn standard single material response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-00-401-5701

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

