## NSN 5320-00-410-0014

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-410-0014

<b>Fastener</b>	I an	ath:
rastener	Len	uuı.

Between 0.575 inches and 0.595 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.172 inches and 0.176 inches

**Shank Style:** 

Self-plugging mechanically locked stem

**Head Major Diameter:** 

Between 0.282 inches and 0.290 inches

**Expansion Device:** 

Serrated stem-type w

**Grip Length:** 

Between 0.376 inches and 0.437 inches

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Special Features:** 

Mat'l aluminum alloy qq-a-430, 5056f

Material:

Aluminum alloy 5056 stem

**Material Specification:** 

Ams6322 assn standard single material response stem

**Surface Treatment:** 

Cadmium stem and chromate stem

**Surface Treatment Specification:** 

Qq-p-416 type 2 cl 2 federal specification single treatment response stem

**Specification Data:** 

80205-nas1739 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.