## NSN 5320-00-413-0463

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-413-0463 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.490 inches and 0.510 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.326 inches and 0.330 inches **Grip Length:** Between 0.245 inches and 0.255 inches **Hardness Rating:** 35.0 rockwell c and 40.0 rockwell c **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees **Heat Treatment:** As fabricated Material: Steel **Material Specification:** Ams 6322 assn standard single material response or ams 6382 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-00-413-0463

Pin-rivet - Page 2 of 2



Fiig:

A528u0