

View Online at <https://aerobasegroup.com/nsn/5320-00-416-9253>

Fastener Length:

Between 0.409 inches and 0.439 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Pull through hollow shank

Head Major Diameter:

Between 0.302 inches and 0.322 inches

Expansion Device:

Plain stem-type t

End Application:

Mrap- cougar ambulance

Grip Length:

Between 0.126 inches and 0.187 inches

Countersink Angle:

Between 120.0 degrees and 124.0 degrees

Material:

Steel comp 1012 or steel comp 1025 or steel comp 1045 or steel comp 1075 mandrel

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Zinc and chromate or cadmium or cadmium and chromate or chromate and phosphate or phosphate zinc mandrel

Surface Treatment Specification:

Qq-z-325 type 2 cl 3 federal specification 1st treatment response or qq-p-416 federal specification 2nd treatment response or qq-p-416 federal specification 3rd treatment response or qq-p-416 federal specification 4th treatment response or mil-p-16232 ty z cl 2 military specification 5th treatment response or mil-p-16232 ty z cl 4b military specification 5th treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.