

View Online at <https://aerobasegroup.com/nsn/5320-00-419-3516>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.573 inches and 0.593 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.077 inches and 0.090 inches

**Width Between Flats:**

Between 0.095 inches and 0.097 inches

**Shank Diameter:**

Between 0.280 inches and 0.281 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.435 inches and 0.460 inches

**Grip Length:**

0.193 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

95000 single pounds per square inch

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-5000 military specification 4th material response or mil-s-5000 military specification 5th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.