

View Online at <https://aerobasegroup.com/nsn/5320-00-421-0078>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.690 inches and 0.710 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.188 inches and 0.189 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.349 inches and 0.354 inches

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Thread Size:**

0.190 inches

**Countersink Angle:**

100.0 degrees

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.