NSN 5320-00-424-3764

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-424-3764

Fastener Length:

Between 1.158 inches and 1.188 inches

Head Style:

Undercut pan no. 2

Head Height:

Between 0.195 inches and 0.205 inches

Shank Diameter:

Between 0.372 inches and 0.374 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.580 inches and 0.627 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.844 inches and 0.907 inches

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

12200 single pounds per square inch

Material:

Steel comp 8740 stem

Material Specification:

Mil-s-6049 military specification 1st material response stem or qq-w-405 comp 8740 federal specification 2nd material response stem

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response body

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.