# NSN 5320-00-438-5637

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-438-5637



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.240 inches and 1.260 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0635 inches and 0.0645 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.933 inches and 0.943 inches

# Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.164 inches

## Shear Strength:

108000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## Collar Style:

Configural type

#### Material:

Titanium alloy

#### Material Specification:

Ams 4971 assn standard single material response

#### **Thread Series Designator:**

Unjc

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-438-5637

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

