## NSN 5320-00-443-6016

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-443-6016 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.120 inches and 2.145 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.6574 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 1.062 inches Tip Diameter: 0.6314 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.490 inches and 1.505 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 49.0 rockwell c **Thread Size:** 0.625 inches **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-00-443-6016

Pin-rivet - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0