

View Online at <https://aerobasegroup.com/nsn/5320-00-444-6433>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.583 inches

Head Style:

Err-090

Head Height:

Between 0.077 inches and 0.087 inches

Width Between Flats:

Between 0.094 inches and 0.095 inches

Shank Diameter:

Between 0.248 inches and 0.249 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Grip Length:

0.193 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 1 class 3 federal specification single treatment response or qq-p-416 type 2 federal specification 1st treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.