NSN 5320-00-446-1610



Blind Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-446-1610 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.255 inches and 0.257 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** Between 0.312 inches and 0.317 inches **Expansion Device:** Threaded sleeve **Grip Length:** 0.312 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Special Features:** Furnished w/o bolt Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve **Surface Treatment:** Cadmium expander **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response expander **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A040a0

NSN 5320-00-446-1610

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.