

View Online at <https://aerobasegroup.com/nsn/5320-00-451-1773>

**Fastener Length:**

Between 0.454 inches and 0.484 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.310 inches and 0.312 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.577 inches and 0.635 inches

**Expansion Device:**

Threaded mandrel

**Grip Length:**

Between 0.282 inches and 0.344 inches

**Hardness Rating:**

30.0 rockwell c and 45.0 rockwell c

**Shear Strength:**

10350 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Specification Data:**

80205-nas1672 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5002 spec.