## NSN 5320-00-451-9167

Blind Rivet - Page 1 of 1

A040a0

Mil-a-8625 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-00-451-9167 Fastener Length: 0.500 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.172 inches and 0.176 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.282 inches and 0.290 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.251 inches and 0.312 inches **Shear Strength:** 935 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Nickel alloy 400 locking ring or nickel alloy r-405 locking ring **Material Specification:** Qq-n-281 federal specification all material responses locking ring **Surface Treatment:** Anodize body or oxide film body **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response body or mil-c-5541 military specification 2nd treatment response body **Specification Data:** 80205-nas1739 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: