## NSN 5320-00-453-4638

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-453-4638 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.033 inches and 1.053 inches **Head Style:** Err-090 **Head Height:** Between 0.060 inches and 0.070 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Grip Length:** Between 0.594 inches and 0.688 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** 1.507 in. Long serrated break stem on shank end Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-00-453-4638

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.